



### Pillared Half Quartz Element





Properties: Quartz infrared heating elements provide medium wave infrared radiation. They are favoured in industrial applications where a more rapid heater response is necessary, including systems with long heater off cycles. The standard quartz heating elements range consists of cassette style elements constructed with polished aluminium clad steel as standard, stainless steel is also an option. These emitters have peak emissions in the medium to long wavelength range.

### Technical specification


Material	Polished aluminium clad steel body with an ironchrome aluminium resistance wire Pressure cast steatite pillar
Heater Voltage	230 V ( <i>standard</i> )
Useful wave-length range	1.5 - 8 $\mu\text{m}$ ( <i>microns</i> ) - Long wave
Dimensions	123.5 x 62.5 x 59.0 mm
Average weight	251 g
Assembly	Recommended radiation distance from heater is 100 - 200 mm
Element spacing	Minimum spacing between elements 5 mm
Average operating life	Up to 10,000 hrs depending on conditions
Standards	CE
Operating temperature	Ensure temperature of aluminium clad steel body does not exceed 500 °C
Note	Element should always be mounted so the quartz glass tubes are horizontal.

### Standard PHQE range

	Mean Surface Temperature °C	Max Power Density kW/m <sup>2</sup>
200 W	542	23.0
250 W	593	28.7
325 W	664	37.3
375 W	690	45.9
500 W	772	57.4



Element supplied with  
Wave Spring and Clip




#### PHQE PILLARED HALF QUARTZ ELEMENT

Tolerances apply, all dimensions mm.  
Heater body manufactured from 0.75 mm  
polished aluminium clad steel ( 500°C max )



25W49



**PHQE** Heat up and cool down curves showing average surface temperature measured with a thermal imaging camera set to an emissivity of 0.7